

# e-STUDIO™ 2330c/2830c

## Configuration Worksheet



### e-STUDIO™ 2330c/2830c Product Configurations

#### Cover Options

A or B	Platen Cover	(A)	KA3511
	RADF (Reversing Auto Document Feeder)	(B)	MR3018

#### Finishing Options (Choose one finisher)

C/F or C/G or C/F/D or C/G/E	Bridge Kit (required with (F) or (G) or (H))	(C)	KN4520
	Hole Punch Unit (for use with (F) only)	(D)	MJ6101
	Hole Punch Unit (for use with (G) only)	(E)	MJ6004
	Multi-Position Finisher	(F)	MJ1101
	Saddle-Stitch Finisher	(G)	MJ1030
	Hanging Finisher	(H)	MJ1031

#### Paper (Choose one: PFP, LCF, or Stand)

I or K or J/K	Large Capacity Feeder	(I)	KD1024
	Additional Cassette (550x1) (for use with (K))	(J)	MY1032
	Paper Feed Pedestal (PFP)	(K)	KD1023
	Stand		STAND4520

#### Other (Not shown)

Coin Controller Wiring Harness	GQ1110
Work Tray	KK3511

#### Advanced Scanning & Software Solutions

eCopy ScanStation OP - Win XP (e-BRIDGE) (3 Years M&S)	TB-SNSTEX P-03
ScanStand Accessory Box (e-BRIDGE)	TB-SNSTAND-00
Re-Rite (OCR Conversion Software)	GB1280
e-BRIDGE Job Separator Utility	GB1410
e-BRIDGE Job Build	GB1420
Re-Search (eDiscovery Software)	(Part Number depends on number of records)

#### Connectivity Options

EFI Controller (not available at launch)	GA1211
Fax Board	GD1250
2nd Line Fax for GD1250	GD1260
Wireless LAN Adapter (802.11 b/g)*	GN1050
Bluetooth Adapter*	GN2010
Wireless Antenna	GN3010
Meta Scan Enabler for e-CONNECT	GS1010
External Interface Enabler for Open Platform	GS1020

#### Security Options

IPsec Enabler	GP1080
Data Overwrite Kit	GP1070
HID SmartCard Authentication	KP2004
MiFare SmartCard Authentication	KP2005

#### Supplies

Staples (for use with (F))	STAPLE2400								
Staples (for use with (G) or (H))	STAPLE2000								
Saddle-Stitch Staples (for use with (G))	STAPLE600								
Toner	<table border="0"> <tr> <td>(C) Cyan</td> <td>TFC28C</td> <td>(M) Magenta</td> <td>TFC28M</td> </tr> <tr> <td>(Y) Yellow</td> <td>TFC28Y</td> <td>(B) Black</td> <td>TFC28K</td> </tr> </table>	(C) Cyan	TFC28C	(M) Magenta	TFC28M	(Y) Yellow	TFC28Y	(B) Black	TFC28K
(C) Cyan	TFC28C	(M) Magenta	TFC28M						
(Y) Yellow	TFC28Y	(B) Black	TFC28K						
Developer	<table border="0"> <tr> <td>(C) Cyan</td> <td>6LE98164200</td> <td>(M) Magenta</td> <td>6LE98164100</td> </tr> <tr> <td>(Y) Yellow</td> <td>6LE98164000</td> <td>(B) Black</td> <td>6LE98164300</td> </tr> </table>	(C) Cyan	6LE98164200	(M) Magenta	6LE98164100	(Y) Yellow	6LE98164000	(B) Black	6LE98164300
(C) Cyan	6LE98164200	(M) Magenta	6LE98164100						
(Y) Yellow	6LE98164000	(B) Black	6LE98164300						

\*Requires Wireless Antenna

Approximate Dimensions: 26" (W) x 28" (D) x 29" (H)  
Power Supply: 115V; 15 Amps ■ Power Consumption: Maximum 1.5kW

Updated November 19, 2008

**TOSHIBA**  
Leading Innovation >>>